



KU1210A Datasheet

Standards and Protocols

- ✚ H.323, SIP, DHCP, TCP/IP, PPPoE
- ✚ G.711, iLBC, G.729
- ✚ USB1.1 and 2.0 compatible

Key features & specifications

- ✚ IN/OUT key for called and received call list
- ✚ ▲/▼ key for the call history list up and down
- ✚ C key for clear
- ✚  and  Key

Features

- ✚ Auto-Run Feature
- ✚ Plug and Dial
- ✚ No sound card required
- ✚ No external power required
- ✚ Saves 1000 incoming call and 1000 dialed numbers
- ✚ LCD Display of Numbers
- ✚ LDC Display of Prepaid Account Balance
- ✚ Full duplex communication
- ✚ Selectable Ring Tone
- ✚ 64MB memory

Operational Environment

- ✚ Operational Temperature: 0 to 50° C (32° to 122° F)
- ✚ Storage Temperature: -30° to 65° C (-22° to 149° F)
- ✚ Humidity: 10% to 90% no dew

Dimensions

- ✚ 123x45x26mm

Electronic Characteristics

- ✚ 5V DC
- ✚ CE, FCC, MIC

Recommended Network Condition

- ✚ Delay: Less than 400ms
- ✚ Jitter: Less than 100ms
- ✚ Package Loss Rate: Less than 10%
- ✚ Required Bandwidth: Minimums 30Kbps

